



СЕРИЯ КГЕ

ДЛЯ ГЛАВНОГО ПОДЪЕМА КАНАТНЫХ ЭЛЕКТРОТЕЛЬФЕРОВ СЕРИИ Т

Технические данные при 380V, 50Hz

Мощность	Тип	Частота на вращене	Режим на работа		Ток	Пусков момент	Спирачен момент	Маса
			CD	SF				
kW		min ⁻¹	%	h ⁻¹	A	Nm	Nm	kg
0,75	КГЕ 1605-6	910	40	240	3,3	16,4	10,8	35
1,5	КГЕ 1608-6 КГЕ II 1608-6	910	40	240	5,8	25,0	23,5	38
3,0	КГЕ 2008-6 КГЕ II 2008-6	920	40	240	11,0	60,5	49	62
4,5	КГЕ 2011-6	920	40	240	12,3	78,0	78	69
8,0	КГЕ 2412-6	920	40	240	24,5	132	105	106
12,5	КГЕ 2714-6 КГЕ 2714Д6	920	40	240	36,0	200	165	155
16,0	КГЕ 3517-6,М6	920	40	240	34,0	380	290	225
25,0	КГЕ 3518Р6,РМ6	950	40	240	47,5	550	450	244
1,1	КГЕ 1605-4	1360	40	240	3,6	15	18	35
2,3	КГЕ 1608-4	1300	40	240	6,0	26	28	38
4,5	КГЕ 2008-4	1400	40	240	12,0	60	70	62
5,5	КГЕ 2011-4	1430	40	240	12,0	80	70	69
7,5	КГЕ 2012-4	1380	40	240	17,0	105	100	79
12,0	КГЕ 2714-4 КГЕ 2714Д4	1430	40	240	28,0	180	130	140
15,5	КГЕ 3517-4,М4	1430	40	240	29,5	240	150	225
22,0	КГЕ 3517Р4,РМ4	1410	40	240	49,0	510	275	225
30,0	КГЕ 3518Р4,РМ4	1440	40	240	55,0	450	360	244
0,15/0,75	КГЕ 2009-30/6	165/930	10/40	240	4,0/4,0	14/15	12	48
0,30/1,5	КГЕ 2110-30/6	165/930	10/40	240	5,2/5,1	30/23	24	57
0,5/3,0	КГЕ 2612-30/6	165/930	10/40	240	10,0/8,5	52	48	106
0,8/4,8	КГЕ 2714-30/6	170/930	10/40	240	15,0/12,0	90	75	136
1,5/8,0	КГЕ 3317-30/6	170/940	10/40	240	30,0/19,0	140	125	201
0,15/1,1	КГЕ 2009-30/4	165/1400	10/40	240	4,0/4,0	14/16	15	48
0,30/2,2	КГЕ 2110-30/4	165/1400	10/40	240	5,5/7,6	30	30	57
0,5/4,5	КГЕ 2612-30/4	165/1400	10/40	240	10,0/11,0	52	55	106
0,8/7,5	КГЕ 2714-30/4	170/1400	10/40	240	15,0/15,0	90	90	136
1,5/12,5	КГЕ 3317-30/4	170/1430	10/40	240	30,0/28,0	140/180	135	201
0,16/0,75	КГЕ 2009-24/6	200/930	25/50	300	3,0/3,4	18	12	48
0,33/1,5	КГЕ 2110-24/6 КГЕ II 2110-24/6	200/930	25/50	300	3,7/5,0	29	24	57
0,7/3,0	КГЕ 2612-24/6 КГЕ II 2612-24/6	210/930	25/50	300	6,0/7,5	52	48	106
1,0/4,8	КГЕ 2714-24/6 КГЕ II 2714-24/6	200/940	25/50	300	11,0/12,0	100	75	136
1,7/8,0	КГЕ 3317-24/6	200/920	25/50	300	15,0/18,0	140	125	201
3,0/13,0	КГЕ 3517-24/6,М24/6	220/960	10/40	240	40,0/30,0	215	180	225
4,0/16,0	КГЕ 3518-24/6,М24/6	210/950	10/40	240	70,0/36,0	360/300	290	244
0,16/1,1	КГЕ 2009-24/4	200/1400	25/50	300	3,0/3,5	16	15	48
0,33/2,2	КГЕ 2110-24/4	200/1400	25/50	300	3,7/6,2	29	30	57
0,7/4,5	КГЕ 2612-24/4	210/1400	25/50	300	6,0/9,5	52	55	106
1,0/7,5	КГЕ 2714-24/4	200/1400	25/50	300	11,0/15,0	100	90	136
1,7/12,5	КГЕ 3317-24/4	200/1430	25/50	300	15,0/23,0	140	135	201
1,9/11,5	КГЕ 3517В24/4,ВМ24/4	225/1410	10/40	240	30,0/25,0	170/180	170	225
2,2/13,0	КГЕ 3517-24/4,М24/4	220/1400	10/40	240	30,0/28,0	200/210	170	225
2,5/15,0	КГЕ 3517N24/4,НМ24/4	220/1400	10/40	240	34,0/32,0	215/225	190	225
4,0/24,0	КГЕ 3518-24/4,М24/4	210/1400	10/40	240	70,0/48,0	360/380	290	244

ЭЛЕКТРОДВИГАТЕЛИ
с тормозом